



# LuxWood

## Engineered Composite Flooring

Plank Size	Thickness	Wear Layer
7.25" x 48"	6.5mm	20Mil

**100% Waterproof**



- Durable UV Ceramic Bead Top Layer
- Heavy Duty 20Mil Wear Layer
- High Definition Decorative Paper
- High Density Rigid Stone Core Technology
- 1.5 EVA Foam Pad



- 100% waterproof floor that looks and feels like real hardwood.
- Can be installed in virtually any room in the home or business including kitchens, bathrooms and basements.
- Quick and easy to install! It features a Unilin® Click locking installation method that can be installed immediately with no acclimation waiting time needed.
- Planks are extra rigid and can be installed directly over most existing subfloors with no sub-floor telegraphing concerns (See installation details for further information regarding your application).
- Does not require glue, nails or underlayment for installation. To cut the product, simply score it with a knife and snap, or use a laminate flooring cutter.
- Luxwood has an anti-microbial coating on top and a pre-attached foam underlayment for a quieter, warmer floor.
- Floorscore® certified and formaldehyde free (meets California Air Resource Board requirements).
- Easy to maintain, simply sweep or wet mop.
- Installation
  - Floating UNILIN® click technology
- Construction
  - 6.5mm Overall thickness (5mm SPC composite core with 1.5mm EVA foam pad attached)
  - Hot-pressed deco layer & 20Mil wear layer / urethane top coat / anti-microbial
- Certifications
  - ASTM E90-09 airborne sound conduction: STC 63 db
  - ASTM E492-09 impact sound conduction: IIC 65 db
  - Carb II compliant (formaldehyde free)
  - FLOORSORE® CERTIFIED
- Warranty information
  - Limited lifetime residential wear layer warranty
  - Limited lifetime structural warranty
  - Limited lifetime waterproof warranty
  - 15 Year limited light commercial wear layer warranty

