

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**DELHI 24x48**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	Precious Stone	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Plain White	Number of Faces/Screens:	1
Thickness in mm:	10MM	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	≤0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	1685
Frost Resistant:	Yes	Thermal Shock Resistance:	YES
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	YES
Chemical Resistance:	ULA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	2
SqFt per Pallet:	387.50	Pounds per Carton:	
Boxes per Pallet:	25	SqFt per Container:	
Pallets per Container:	28		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".