## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 



SERIES NAME	Verena
5211125 TV 1112	Verena

TECHNICAL CHARACTERISTICS					
Available Formats:	12x24				
Style Description:	English Marble	Glaze Application Method:	H.D.I.T. Inkjet		
Visual Characteristics:	Soft Marble	Number of Faces/Screens:	15		
Thickness in mm:	9mm	Number of Punches/Molds:	1		
Modular Suitability:	No	Body Type:	Porcelain		
Application:	Residential	Color Body Unglazed:			
Recycled Content: Post or Pre Customer	NA	Surface Type:	Matte		
Rectified:	No	Recommended Grout Joint:	3mm		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	0.2%	Static COF:				
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.63			
Scratch Hardness (MOHS)	7	Breaking Strength:	421			
Frost Resistant:	Yes	Thermal Shock Resistance:	NA			
PEI/Abrasion Resistance:	IV	Deep Abrasion Test	No			
		<175mm <sup>2</sup> :				
Chemical Resistance:						

PACKING INFORMATION -	Please inquire with Customer Service for additional sizes		
SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	496.00	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:	28		

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".