## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 





SERIES NAME ASIA

TECHNICAL CHARACTERISTICS					
Available Formats:	9x45				
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet		
Visual Characteristics:		Number of Faces/Screens:	15		
Thickness in mm:	9 mm	Number of Punches/Molds:	1		
Modular Suitability:	No	Body Type:	Porcelain		
Application:	Residential/Commercial	Color Body Unglazed:	Sand White		
Recycled Content:	4%	Surface Type:	Matte/Flat		
Post or Pre Customer					
Rectified:	Yes	Recommended Grout Joint:	2 mm		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	<.5%	Static COF:				
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	<u>&gt;0.4</u>			
Scratch Hardness (MOHS)	5	Breaking Strength:	>1500N			
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes			
PEI/Abrasion Resistance:	4	Deep Abrasion Test	No			
		<175mm <sup>2</sup> :				
Chemical Resistance:	>1500N					

PACKING INFORMATION -	Please inquire with Customer Service for additional sizes		
SqFt per Carton:	19.59	Pieces per Carton:	9
SqFt per Pallet:	940.32	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	16		

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4% to 3/16% but no less than 1/8%.