NEW PRODUCT SERIES

Technical Information Spec-sheet



NAME	SERIES	ASIAGO

TECHNICAL CHARACTERISTICS				
Available Formats:	12x24, 2x2 Mosaic & 3x24 Bullnose			
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet	
Visual Characteristics:	Crosscut Stone	Number of Faces/Screens:	18	
Thickness in mm:	9	Number of Punches/Molds:	1	
Modular Suitability:	No	Body Type:	Porcelain	
Application:	Residential / Commercial	Color Body Unglazed:	No	
Recycled Content:	≥6	Surface Type:	Matte / Flat	
Post or Pre Customer				
Rectified:		Recommended Grout Joint:	>3mm	

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	≤0.5	Static COF:				
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.37			
Scratch Hardness (MOHS)	≥6	Breaking Strength:	U7 Class			
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant			
PEI/Abrasion Resistance:	IV	Deep Abrasion Test	Yes			
		<175mm ² :				
Chemical Resistance:	Yes					

PACKING INFORMATION -	12x24 Please inquire with Customer Service for additional sizes		
SqFt per Carton:	14.53	Pieces per Carton:	7
SqFt per Pallet:	871.8	Pounds per Carton:	48.67
Boxes per Pallet:	60	SqFt per Container:	17436.00
Pallets per Container:	20		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".