

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Atlantis

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 1x3 Mosaic 12x12 Sheet, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Travertine	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:		Number of Faces/Screens:	32
Thickness in mm:	10.5	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Satin
Rectified:	Rectified	Recommended Grout Joint:	3mm minimum

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.62
Scratch Hardness (MOHS)	5	Breaking Strength:	S \geq 2000 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Yes		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	6
SqFt per Pallet:	465.20	Pounds per Carton:	49.543
Boxes per Pallet:	40	SqFt per Container:	13025.60
Pallets per Container:	28		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".