

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

ATLAS

TECHNICAL CHARACTERISTICS

Available Formats:	11X22		
Style Description:	Light Colored Stone look	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Cross Cut Travertine	Number of Faces/Screens:	12
Thickness in mm:	8.3mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42 Wet
Scratch Hardness (MOHS)	5	Breaking Strength:	In compliance
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.22	Pieces per Carton:	10
SqFt per Pallet:	1033.20	Pounds per SqFt:	
Boxes per Pallet:	60	SqFt per Container:	
Pallets per Container:	15		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".