

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Bianco Palace**

## TECHNICAL CHARACTERISTICS

Available Formats:	32x32		
Style Description:	Polished White	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Polished White	Number of Faces/Screens:	1
Thickness in mm:	9.2 MM	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	No	Recommended Grout Joint:	2MM   0.08

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	Not Tested
Scratch Hardness (MOHS)	3	Breaking Strength:	>1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	>GLB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	20.78	Pieces per Carton:	3
SqFt per Pallet:	664.80	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".