

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Cashmere

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 3x12, 3x24 Bullnose, Rhomboid Mosaic 9x10.75 Sheet, Wave Mosaic 11.75x11.75 Sheet		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	64
Thickness in mm:	10 mm	Number of Punches/Molds:	2
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	Pre - 11.5%	Surface Type:	Satin
Rectified:	Rectified	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.2%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.43
Scratch Hardness (MOHS)	>5	Breaking Strength:	>42 N/MM <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	6.00
SqFt per Pallet:	465.20	Pounds per Carton:	52.80
Boxes per Pallet:	40.00	SqFt per Container:	1016.40
Pallets per Container:	22		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".