

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME	Cave Rock
-------------	-----------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24		
Style Description:	Marble Look	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	Forte 40/ Pietra Santa 60
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	>40%	Surface Type:	Textured
Rectified:	Yes	Recommended Grout Joint:	2 mm

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<0.2%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.50
Scratch Hardness (MOHS)	5	Breaking Strength:	>40 N/mm
Frost Resistant:	Yes	Thermal Shock Resistance:	Conform
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Conform		

PACKING INFORMATION - <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	13.13	Pieces per Carton:	7
SqFt per Pallet:	472.68	Pounds per Carton:	
Boxes per Pallet:	36	SqFt per Container:	
Pallets per Container:	27		

**Note:**

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".