

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**CUMBRIA WALL**

## TECHNICAL CHARACTERISTICS

Available Formats:	14x36		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	11
Thickness in mm:	9.6mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	5	Surface Type:	Flat
Rectified:	Yes	Recommended Grout Joint:	1mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	5	Breaking Strength:	>600N
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Class 5		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17	Pieces per Carton:	5
SqFt per Pallet:	680	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	23		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**CUMBRIA FLOOR**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	10
Thickness in mm:	9.2mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	NA	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	1mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	-0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	.71
Scratch Hardness (MOHS)	8	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	3
SqFt per Pallet:	465.20	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	26		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".