

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Hematite**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24: 24x48		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	12x24: 36 24x48: 9
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	UGL Matte Finish
Recycled Content: Post or Pre Customer	NA	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	-0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	63
Scratch Hardness (MOHS)	6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Compliant
PEI/Abrasion Resistance:	V+	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	496.00	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:	22		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".