

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

High Sierra

TECHNICAL CHARACTERISTICS

Available Formats:	9x34.5, 9x48		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Wood Plank	Number of Faces/Screens:	17
Thickness in mm:	10	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	-0.5%	Static COF:	Dry: 0.64 Wet: 0.60
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.68	Pieces per Carton:	6
SqFt per Pallet:	656.64	Pounds per Carton:	55.13
Boxes per Pallet:	48	SqFt per Container:	11819.52
Pallets per Container:	18		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".