

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

LARVIC

## TECHNICAL CHARACTERISTICS

Available Formats:	9X48		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:		Recommended Grout Joint:	1mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	.68
Scratch Hardness (MOHS)		Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Minimum GB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqM per Carton:	12.05	Pieces per Carton:	4
SqM per Pallet:	578.4	Pounds per Carton:	
Boxes per Pallet:	48	SqM per Container:	11,568
Pallets per Container:	23		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".