

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Madras

TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 32x32, 24x24, 12x24		
Style Description:		Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	24x48 (4), 32x32 (4), 24x24 (8), 12x24 (6)
Thickness in mm:	9 mm for all sizes	Number of Punches/Molds:	Plain Punch
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Regular body with glazed surface
Recycled Content: Post or Pre Customer		Surface Type:	Matte & Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	Suitable as per Weather condition

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	0.52-0.61
Scratch Hardness (MOHS)	5	Breaking Strength:	2689.23 N APPROX
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	YES		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes 12x24*

SqFt per Carton:	9.69	Pieces per Carton:	5
SqFt per Pallet:	620.16	Pounds per Carton:	
Boxes per Pallet:	64	SqFt per Container:	
Pallets per Container:	23		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".