

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**MARMI**

## TECHNICAL CHARACTERISTICS

Available Formats:	32x32 & 3x32 Bullnose		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Carrara	Number of Faces/Screens:	N/A
Thickness in mm:	11mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	Above 20%	Surface Type:	Matte / Flat
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Passes
Chemical Resistance:	Yes		

## PACKING INFORMATION - 24x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	12.11	Pieces per Carton:	2
SqFt per Pallet:	484.38	Pounds per SqFt:	5.05 Lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".