

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Mayfair

TECHNICAL CHARACTERISTICS

Available Formats:	24x48, 24x24, 16x32, 10.5x32, 12x24, 4x12, 3x24 Bullnose, 3x12 Bullnose		
Style Description:	Matte & Polished	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	40-56
Thickness in mm:	9.8	Number of Punches/Molds:	
Modular Suitability:		Body Type:	
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte & Polished
Rectified:	Rectified	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤0.5%	Static COF:	Wet: ≥0.50 Dry: ≥0.70
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42 (Matte only)
Scratch Hardness (MOHS)	6	Breaking Strength:	≥500
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class A - Res.		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	434.00	Pounds per Carton:	68.665
Boxes per Pallet:	28.00	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".