

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MOUNT TIEDE

TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 12x12, 10x16 Wall, 2x2 Mosaic 12x12 Sheet, 3x12 Floor Bullnose, 2x10 Wall Bullnose		
Style Description:	Stone	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Rustic	Number of Faces/Screens:	4
Thickness in mm:	8mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic (>.5%)
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16th

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	> .5%	Static COF:	Wet: .52 Dry: .69
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	6.5	Breaking Strength:	Min 800 Applied
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Required		

PACKING INFORMATION - 18x18 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.44	Pieces per Carton:	8
SqFt per Pallet:	906.88	Pounds per Carton:	65.4 Lbs
Boxes per Pallet:	52	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".