

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Nuance

TECHNICAL CHARACTERISTICS

Available Formats:	24x48*, 16x32, 12x24, Universal Rhomboid 9x11 Sheet, 2x2 Polished Mosaic 12x12 Sheet, & 3x24 Floor Bullnose		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	24x48(10), 16x32(20), 12x24(40)
Thickness in mm:	9.5mm-10mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Polished
Rectified:	Yes	Recommended Grout Joint:	

*Available in Beige, Grey, and White only

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	Wet: .29 Dry: .70
Scratch Hardness (MOHS)	6-8	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	III-V	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Resist		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.78	Pieces per Carton:	4
SqFt per Pallet:	289.38	Pounds per Carton:	599.43
Boxes per Pallet:	21	SqFt per Container:	13022.10
Pallets per Container:	45		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".