

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	OZARK
-------------	---------------	--------------

TECHNICAL CHARACTERISTICS			
Available Formats:	6x36		
Style Description:	Wood	Glaze Application Method:	INKJET
Visual Characteristics:	Modern Wood	Number of Faces/Screens:	14
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	0	Surface Type:	
Rectified:	No	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	0.2	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.63
Scratch Hardness (MOHS)		Breaking Strength:	480
Frost Resistant:	YES	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

PACKING INFORMATION - 18x18 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	13.13	Pieces per Carton:	9
SqFt per Pallet:	472.68	Pounds per Carton:	
Boxes per Pallet:	36	SqFt per Container:	
Pallets per Container:	28		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".