

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

RIVER

TECHNICAL CHARACTERISTICS

Available Formats:	12x48		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Travertine	Number of Faces/Screens:	3
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commerical	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	Yes

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	1685
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	<175MM2
Chemical Resistance:	ULA		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:		Pieces per Carton:	2
SqFt per Pallet:	387.50	Pounds per Carton:	
Boxes per Pallet:	25	SqFt per Container:	
Pallets per Container:	28		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".