

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Rock

TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 18x18, 12x24		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Rapolano Stone	Number of Faces/Screens:	24x24(30), 18x18(30), 12x24 (60)
Thickness in mm:	9mm	Number of Punches/Molds:	2
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	Pre Customer 30% and 4% Sold Materials	Surface Type:	Matte and Textured
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>.42
Scratch Hardness (MOHS)	7	Breaking Strength:	40N/sq mm
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	UA-UHA-UHA		

PACKING INFORMATION - 18x18 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.25	Pieces per Carton:	7
SqFt per Pallet:	793.00	Pounds per Carton:	
Boxes per Pallet:	52.00	SqFt per Container:	
Pallets per Container:	18.50		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".