NEW PRODUCT SERIES

Technical Information Spec-sheet



SERIES NAME	SOHO

TECHNICAL CHARACTERISTICS				
Available Formats:	8x24*, 8x16*, 4x12*, 4x16, 3x6, 3x6, 4x8 & 3x6 Wall Bullnose, 2x2 Dot-Mount 12x12			
	Mosaic, Arabesque Mosaic 9.75x1125 Sheet, Convex Mosaic 12.5x9.75 Sheet.			
Style Description:	Fume	Glaze Application Method:	Rotocolor	
Visual Characteristics:	Subway Tile	Number of Faces/Screens:	N/A	
Thickness in mm:	5/16"	Number of Punches/Molds:	N/A	
Modular Suitability:	Yes	Body Type:	Ceramic	
Application:	Residential/Commercial	Color Body Unglazed:	No	
Recycled Content:	N/A	Surface Type:	Shiny/Gloss & Matte White	
Post or Pre Customer				
Rectified:	No	Recommended Grout Joint:	N/A	

^{*}White Glossy Only

PRODUCT TESTING INFORMATION					
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)					
Water Absorption:	1.15%	Static COF:	Not rated		
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A		
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A		
Frost Resistant:	No	Thermal Shock Resistance:	N/A		
PEI/Abrasion Resistance:	Not Rated	Deep Abrasion Test <175mm ² :	N/A		
Chemical Resistance:	N/A		•		

PACKING INFORMATION - 4x16 Please inquire with		Customer Service for additional sizes	
SqFt per Carton:	11	Pieces per Carton:	25
SqFt per Pallet:	770	Pounds per Carton:	33.00 Lbs
Boxes per Pallet:	70	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".