

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Torino

TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 13x13, 12x24, 3x3 Mosaic 12x12 Sheet, 3x13 Bullnose		
Style Description:	Stone	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	8.636	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	≤0.7
Scratch Hardness (MOHS)	6	Breaking Strength:	≥350
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class B		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.22	Pieces per Carton:	6
SqFt per Pallet:	421.72	Pounds per Carton:	65.204
Boxes per Pallet:	26	SqFt per Container:	9277.84
Pallets per Container:	22		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".