

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME	ATLAS
-------------	-------

TECHNICAL CHARACTERISTICS			
Available Formats:	11X22		
Style Description:	Light Colored Stone look	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Cross Cut Travertine	Number of Faces/Screens:	12
Thickness in mm:	8.3mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	< .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42 Wet
Scratch Hardness (MOHS)	5	Breaking Strength:	In compliance
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x24 <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	17.22	Pieces per Carton:	10
SqFt per Pallet:	1033.20	Pounds per SqFt:	
Boxes per Pallet:	60	SqFt per Container:	
Pallets per Container:	15		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.