

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

AEQUA

TECHNICAL CHARACTERISTICS

Available Formats:	12x48	Glaze Application Method:	HDIT Inkjet
Style Description:	Wood	Number of Faces/Screens:	30
Visual Characteristics:	Wood	Number of Punches/Molds:	2
Thickness in mm:	10.50 mm	Body Type:	Porcelain (<.5%)
Modular Suitability:	Yes	Color Body Unglazed:	Yes
Application:	Residential/Commercial	Surface Type:	Matte/Slight Texture
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	Minimum 1/8"
Rectified:	Yes		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	Wet: 0.63 Dry: 0.65
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	≥ 40/N sq mm
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Class A		

PACKING INFORMATION

SqFt per Carton:	15.49	Pieces per Carton:	4
SqFt per Pallet:	278.82	Pounds per SqFt:	4.5 lbs
Boxes per Pallet:	18	SqFt per Container:	12965.13
Pallets per Container:	22.5 (27 ton container)		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.