

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

NAME	SERIES	ASIAGO
------	--------	--------

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24, 2x2 Mosaic & 3x24 Bullnose		
Style Description:	Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Crosscut Stone	Number of Faces/Screens:	18
Thickness in mm:	9	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	≥6	Surface Type:	Matte / Flat
Rectified:		Recommended Grout Joint:	>3mm

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	≤0.5	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.37
Scratch Hardness (MOHS)	≥6	Breaking Strength:	U7 Class
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION - 12x24 Please inquire with Customer Service for additional sizes			
SqFt per Carton:	14.53	Pieces per Carton:	7
SqFt per Pallet:	871.8	Pounds per Carton:	48.67
Boxes per Pallet:	60	SqFt per Container:	17436.00
Pallets per Container:	20		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.