NEW PRODUCT SERIES

Technical Information Spec-sheet



SERIES NAME	Atelier

TECHNICAL CHARACTERISTICS					
Available Formats:	9x48, 9x34.5				
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet		
Visual Characteristics:		Number of Faces/Screens:	15		
Thickness in mm:	10mm	Number of Punches/Molds:			
Modular Suitability:		Body Type:	Porcelain		
Application:	Residential/ Commercial	Color Body Unglazed:			
Recycled Content:		Surface Type:	Matte		
Post or Pre Customer					
Rectified:	No	Recommended Grout Joint:			

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	0.5%	Static COF:				
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>.42			
Scratch Hardness (MOHS)		Breaking Strength:				
Frost Resistant:	Yes	Thermal Shock Resistance:				
PEI/Abrasion Resistance:	IV	Deep Abrasion Test				
		<175mm ² :				
Chemical Resistance:						

PACKING INFORMATION -	9x48 Please inquire with Customer Service for additional sizes			
SqFt per Carton:	18.10	Pieces per Carton:	6	
SqFt per Pallet:	760.20	Pounds per Carton:	70.41	
Boxes per Pallet:	42	SqFt per Container:	12923.40	
Pallets per Container:	17			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.