

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Avorio

TECHNICAL CHARACTERISTICS

Available Formats:	12x24	Glaze Application Method:	H.D.I.T. Inkjet
Style Description:	Marble	Number of Faces/Screens:	Bianco (42), De brescia (40), & Grigio (32)
Visual Characteristics:	Marble	Number of Punches/Molds:	1
Thickness in mm:	10mm	Body Type:	Porcelain
Modular Suitability:	No	Color Body Unglazed:	N/A
Application:	Residential/Commercial	Surface Type:	Matte/Flat
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	ANSI Standards
Rectified:	No		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	250 lbs or greater
Frost Resistant:	Yes	Thermal Shock Resistance:	resistant
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Resistant		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.71	Pieces per Carton:	8
SqFt per Pallet:	628.40	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	16		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.