

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Basic Hex

TECHNICAL CHARACTERISTICS

Available Formats:	8.75x10		
Style Description:	Solid Color	Glaze Application Method:	
Visual Characteristics:	Solid Color Hex	Number of Faces/Screens:	1
Thickness in mm:	10 mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified or Pressed	Pressed	Recommended Grout Joint:	1/32"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	$E \leq 0.5\%$	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥ 0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	≥ 1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	resistant as per standard ISO 10545 - 9
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GA - GHA		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.