

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Bella Legno

TECHNICAL CHARACTERISTICS

Available Formats:	12x48		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	21
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Gres Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	2%	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	2 mm/ 3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.40
Scratch Hardness (MOHS)	5	Breaking Strength:	>R+ 35N/mm2 (maggiore/uguale)
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Yes		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	4
SqFt per Pallet:	279.00	Pounds per Carton:	
Boxes per Pallet:	18	SqFt per Container:	
Pallets per Container:	44		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.