NEW PRODUCT SERIES

Technical Information Spec-sheet



		SERIES NAME	CALACATTA WHITE
--	--	-------------	-----------------

TECHNICAL CHARACTERISTICS					
Available Formats:	18x18, 12x12, 2x2 Mosaic 1	18x18, 12x12, 2x2 Mosaic 12x12 Sheet, 8x12 Wall, 3x12 Floor Bullnose, 2x8 Wall Bullnose			
Style Description:	Honed Marble	Glaze Application Method:	HDIT Inkjet		
Visual Characteristics:	Calacatta	Number of Faces/Screens:	18x18: 11; 12x12: 15		
Thickness in mm:	N/A	Number of Punches/Molds:	N/A		
Modular Suitability:	No	Body Type:	Ceramic (>.5%)		
Application:	Residential	Color Body Unglazed:	No		
Recycled Content:	N/A	Surface Type:	Matte		
Post or Pre Customer					
Rectified:	No	Recommended Grout Joint:	No less than 3/16th		

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	> .5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A
Frost Resistant:	No	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	Resistant		

PACKING INFORMATION -18x18 Please inquire with Customer Service for additional sizes			
SqFt per Carton:	21.84	Pieces per Carton:	10
SqFt per Pallet:	960.96	Pounds per SqFt:	3.14
Boxes per Pallet:	44	SqFt per Container:	18,258.24
Pallets per Container:	19		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.