

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

CHALET

## TECHNICAL CHARACTERISTICS

Available Formats:	6x36	Glaze Application Method:	HDIT Inkjet
Style Description:	Rustic/Reclaimed	Number of Faces/Screens:	27
Visual Characteristics:	Wood	Number of Punches/Molds:	9
Thickness in mm:	10 mm	Body Type:	Porcelain (<.5%)
Modular Suitability:	Yes	Color Body Unglazed:	Yes
Application:	Residential/Commercial	Surface Type:	Matte
Recycled Content: Post or Pre Customer	N/A	Recommended Grout Joint:	Minimum 1/8"
Rectified:	Yes		

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<.5%	Static COF:	Wet: 0.65 Dry: 0.9
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	N/A
Scratch Hardness (MOHS)	7	Breaking Strength:	N/A
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Yes		

## PACKING INFORMATION

SqFt per Carton:	13.07	Pieces per Carton:	9
SqFt per Pallet:	627.36	Pounds per SqFt:	4.59
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	N/A		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*