

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Chelsea

## TECHNICAL CHARACTERISTICS

Available Formats:	4x8, 4x8 Bullnose, 4x8 Corner, 4x8 Deco		
Style Description:	Brick	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Reclaimed Brick	Number of Faces/Screens:	
Thickness in mm:	-/+ 5%	Number of Punches/Molds:	
Modular Suitability:		Body Type:	
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.5%	Static COF:	0.96 D / 0.83 W
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	
Scratch Hardness (MOHS)	8	Breaking Strength:	S $\geq$ 1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	5.39	Pieces per Carton:	25
SqFt per Pallet:	517.44	Pounds per Carton:	22.69
Boxes per Pallet:	96	SqFt per Container:	
Pallets per Container:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*