

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Cloudcroft

TECHNICAL CHARACTERISTICS

Available Formats:	24x48		
Style Description:	Stone	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx Look	Number of Faces/Screens:	6
Thickness in mm:	9 mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Commercial/Residential	Color Body Unglazed:	Not colorbody but produced on System Press
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished/Flat
Rectified:	Yes	Recommended Grout Joint:	1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.49	Pieces per Carton:	2
SqFt per Pallet:	464.70	Pounds per Carton:	
Boxes per Pallet:	30	SqFt per Container:	
Pallets per Container:	30		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.