

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Craft

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 3x24 Floor Bullnose, 2x2 Mosaic 12x12 Sheet, and Universal Geo Mosaic 12x12 Sheet		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Fabric	Number of Faces/Screens:	16
Thickness in mm:	10mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Color Body
Recycled Content: Post or Pre Customer	40%	Surface Type:	Textured, Matte
Rectified:	Rectified	Recommended Grout Joint:	1/8"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≥0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	≥250lbf
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	ASTM C650 RESISTANT		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.67	Pieces per Carton:	7
SqFt per Pallet:	437.44	Pounds per Carton:	62.83
Boxes per Pallet:	32	SqFt per Container:	9186.24
Pallets per Container:	21		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.