

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

CRAYONS

TECHNICAL CHARACTERISTICS

Available Formats:	3x12		
Style Description:	Pure White Body	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Fume or "Subway"	Number of Faces/Screens:	
Thickness in mm:	10 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	Glaze Pure White Body
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	No, Pressed	Recommended Grout Joint:	2MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Between 10%-20%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)		Breaking Strength:	17 N/mm ²
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	N/A	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class A		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	4.25	Pieces per Carton:	20
SqFt per Pallet:	306.00	Pounds per Carton:	
Boxes per Pallet:	72.00	SqFt per Container:	
Pallets per Container:	28.00		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.