

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

H-LINE

TECHNICAL CHARACTERISTICS

| | | | |
|---|---|---------------------------|-------------------------|
| Available Formats: | 4x16, 3x6, 1x1 Mosaic 12x12 Sheet, 1/4x8 Pencil Bullnose, 3x6 Long & Short Bullnose | | |
| Style Description: | Fume | Glaze Application Method: | Rotocolor |
| Visual Characteristics: | Subway Tile | Number of Faces/Screens: | N/A |
| Thickness in mm: | N/A | Number of Punches/Molds: | N/A |
| Modular Suitability: | Yes | Body Type: | Gres Porcelain (.1-.5%) |
| Application: | Residential/Commercial | Color Body Unglazed: | No |
| Recycled Content: Post or Pre Customer | N/A | Surface Type: | Shiny/Gloss |
| Rectified: | Yes | Recommended Grout Joint: | N/A |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|-----------|--|-----------|
| Water Absorption: | .1-.5% | Static COF: | Not rated |
| Shade Variation (1, 2, 3, 4) | V2 | Dynamic COF: | N/A |
| Scratch Hardness (MOHS) | N/A | Breaking Strength: | N/A |
| Frost Resistant: | No | Thermal Shock Resistance: | N/A |
| PEI/Abrasion Resistance: | Not Rated | Deep Abrasion Test <175mm ² : | N/A |
| Chemical Resistance: | N/A | | |

PACKING INFORMATION - 4x16 *Please inquire with Customer Service for additional sizes*

| | | | |
|------------------------|-----|---------------------|-----------|
| SqFt per Carton: | 11 | Pieces per Carton: | 25 |
| SqFt per Pallet: | 770 | Pounds per Carton: | 36.85 Lbs |
| Boxes per Pallet: | 70 | SqFt per Container: | N/A |
| Pallets per Container: | N/A | | |

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.