NEW PRODUCT SERIES

Technical Information Spec-sheet



SERIES NAME	Havana

TECHNICAL CHARACTERISTICS					
Available Formats:	16x16, 8x16, 8x8, 8x8 Deco, 4x8, 4x8 Deco, 2x11, 4x8 BN, 4" Corner, 2" Corner, Stair Tread,				
Style Description:	Weathered Brick	Glaze Application Method:	H.D.I.T Inkjet		
Visual Characteristics:	Cuban Inspired Weathered	Number of Faces/Screens:	See Specifications on website		
Thickness in mm:	10	Number of Punches/Molds:	10		
Modular Suitability:	Yes	Body Type:	Porcelain		
Application:	Residential/Commercial	Color Body Unglazed:	No		
Recycled Content: Post or Pre Customer	0%	Surface Type:	Textured		
Rectified:		Recommended Grout Joint:	3/16"		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	<0.05%	Static COF:				
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>0.42			
Scratch Hardness (MOHS)	7	Breaking Strength:	>450LB			
Frost Resistant:	Yes	Thermal Shock Resistance:				
PEI/Abrasion Resistance:	IV	Deep Abrasion Test	No			
		<175mm ² :				
Chemical Resistance:	Class GA					

PACKING INFORMATION - 8x16 Please inquire with Customer Service for additional sizes				
SqFt per Carton:	11.2	Pieces per Carton:	13	
SqFt per Pallet:	604.80	Pounds per Carton:	45.81	
Boxes per Pallet:	54	SqFt per Container:	13305.60	
Pallets per Container:	22			

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.