

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME **LARVIC**

TECHNICAL CHARACTERISTICS

Available Formats:	9x48, 6x36 (Special Order)		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:		Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:		Recommended Grout Joint:	1mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.54
Scratch Hardness (MOHS)		Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Minimum GB		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqM per Carton:	12.05	Pieces per Carton:	4
SqM per Pallet:	578.4	Pounds per Carton:	
Boxes per Pallet:	48	SqM per Container:	11,568
Pallets per Container:	23		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.