



## Luxwood Technical Specifications

---

**Description:** Luxury Engineered Vinyl Plank, Floating Floor with Attached EVA Pad

**Warranty:** Limited Lifetime Residential Wear Warranty  
15 Year Limited Lt. Commercial Warranty

**Installation:** Unilin Click - Float, Glue Down

**Construction:** Stone Core Composite (Limestone with some virgin PVC)  
Luxwood – 20 mil wear layer with 1.5mm EVA Pad

**Size/Packing:** Luxwood – 7.25” x 48” x 6.5mm Planks  
24.14 sf/box, 10 planks/box, 53.20 lbs/box, 45 boxes/pallet

**Wear Finish:** 2 layered Ceramic Bead, Aluminum Oxide Finish with Antimicrobial surface

### TEST DATA

ASTM – E90-09 Airborne Sound Conduction:	STC 63 db
ASTM – E492-09 Impact Sound Conduction:	IIC 65 db / $\Delta$ IIC 21
ANSI A137.1 Dynamic Coefficient of Friction Test:	0.52 DCOF
ASTM F970-00 Static Load	1500 PSI (0.008 of an inch)
ASTM F 1515 Color Resistance to Light:	Meets <8.0 $\Delta$ E Requirement
ASTM F 1514 Color Resistance to Heat:	Meets <8.0 $\Delta$ E Requirement

