

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

MILANO

## TECHNICAL CHARACTERISTICS

Available Formats:	8.5x9.75		
Style Description:	Embossed Hex	Glaze Application Method:	
Visual Characteristics:	Embossed Hex	Number of Faces/Screens:	
Thickness in mm:		Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Off White
Recycled Content: Post or Pre Customer		Surface Type:	Satin/Flat
Rectified or Pressed	Pressed	Recommended Grout Joint:	2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	>1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Resistant		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*