NEW PRODUCT SERIES

Technical Information Spec-sheet

International Wholesale Tile, LLC

SERIES NAME	**REAL CHARM**

TECHNICAL CHARACTERISTICS			
Available Formats:	6x36, 3x24, 10x11 Hex		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Reclaimed Wood	Number of Faces/Screens:	6x36 (39), 3x24(40), 10x11 Hex (24)
Thickness in mm:	10 mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	3	Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	E<0,1 BLA- GL	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0,42
Scratch Hardness (MOHS)	>6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	resistent
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm^2:	No
Chemical Resistance:	Class A-LA-HA (No Hydrofluoric acid		

PACKING INFORMATION - ***Please inquire with Customer Service for additional sizes***			
SqFt per Carton:	13.13	Pieces per Carton:	9
SqFt per Pallet:	630.24	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	22		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com