

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	SAMURAI
------	--------	---------

TECHNICAL CHARACTERISTICS			
Available Formats:	3X15 Ledger Field Tile		
Style Description:		Glaze Application Method:	HDIT Inkjet
Visual Characteristics:		Number of Faces/Screens:	54
Thickness in mm:	120	Number of Punches/Molds:	2
Modular Suitability:		Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	2MM

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	0.2	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	8	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:		Pieces per Carton:	26
SqFt per Pallet:		Pounds per Carton:	
Boxes per Pallet:	70	SqFt per Container:	
Pallets per Container:	N/A		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.