

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME **Savannah**

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood Plank	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	12
Thickness in mm:	10 mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte, Textured
Rectified:	No	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	≥0.60
Scratch Hardness (MOHS)	9	Breaking Strength:	≥2900 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GA / GLA		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.08	Pieces per Carton:	9
SqFt per Pallet:	627.84	Pounds per Carton:	58.34 lbs
Boxes per Pallet:	48	SqFt per Container:	11301.12
Pallets per Container:	18		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.