

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

SHUI WALL

TECHNICAL CHARACTERISTICS

Available Formats:	14x36		
Style Description:	Zen Design	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	10
Thickness in mm:	9.6mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	5	Surface Type:	Matte, Satin
Rectified:	Yes	Recommended Grout Joint:	1mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	5	Breaking Strength:	>600N
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class 5		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17	Pieces per Carton:	5
SqFt per Pallet:	680	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	23		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.