

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Simple

TECHNICAL CHARACTERISTICS

Available Formats:	8x12		
Style Description:	Plain White	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	6	Number of Punches/Molds:	Plain Punch
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	No	Recommended Grout Joint:	TCNA

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	13-15%	Static COF:	
Shade Variation (1, 2, 3, 4)		Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	After Check by QC Team
Frost Resistant:		Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.33	Pieces per Carton:	16
SqFt per Pallet:	1239.60	Pounds per Carton:	
Boxes per Pallet:	120	SqFt per Container:	
Pallets per Container:	22		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.