

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Slide

## TECHNICAL CHARACTERISTICS

Available Formats:	8x24 & 4x12		
Style Description:	Backlit Effect Wall Tile	Glaze Application Method:	
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential / Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	Not Rated
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	N/A	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - 4x12 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	10.98	Pieces per Carton:	34
SqFt per Pallet:	878.40	Pounds per Carton:	
Boxes per Pallet:	80	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".