

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TRUNK

TECHNICAL CHARACTERISTICS

Available Formats:	9X48		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	27
Thickness in mm:	9.5mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte/Textured
Rectified:	No	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	35-45N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	RESISTS
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	14.85	Pieces per Carton:	5
SqFt per Pallet:	668.25	Pounds per Carton:	
Boxes per Pallet:	45	SqFt per Container:	
Pallets per Container:	19		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.