

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Verena**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	English Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Soft Marble	Number of Faces/Screens:	15
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	NA	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.2%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.63
Scratch Hardness (MOHS)	7	Breaking Strength:	421
Frost Resistant:	Yes	Thermal Shock Resistance:	NA
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	8
SqFt per Pallet:	496.00	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:	28		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*